



**P O R T O L A**  
Paints & Glazes

PROUDUCT NAME

FLORENTINE GLAZE

Portola Paints & Glazes

8213 W 3<sup>rd</sup> Street

Los Angeles, CA 90048

ph: 323.655.2211

[www.portolapaints.com](http://www.portolapaints.com)

PRODUCT DESCRIPTION

Portola's Florentine Glaze is an incredibly beautiful, high gloss glaze that is used in combination with Portola's Zero VOC Eggshell acrylic to give an intensity and translucency to interior surfaces. Florentine Glaze is similar to traditional oil-based and scumble glazes except that it has been created in a water based medium for a healthier application and more environmentally friendly product. Florentine Glaze may be used for a variety of effects, including ragging, stippling, dragging and sponging. Florentine Glaze is available in a wide range of stock and custom colors.

SUGGESTED APPLICATIONS

Portola's Florentine Glaze is designed to be applied over Portola's Zero VOC Eggshell acrylic. Florentine Glaze is intended for use on most paintable interior and exterior surfaces including dry wall, plaster, wood and masonry.

LIMITATIONS

Florentine Glaze should not be applied below 50 degrees Fahrenheit.

PREPARATION

All loose and defective concrete or masonry and any surface contaminants such as dirt, grease, oil, acid, mildew, chalk, excessive salt, and efflorescence that adversely affect product adhesion and performance must be removed. Fresh cementitious substrates should be cured a minimum of 21 days prior to application. Painted semi-gloss surfaces should be de-glossed and cleaned prior to applying Portola's All Purpose Base Coat. Spot prime all repaired areas using Portola's All Purpose Base Coat. Allow to dry for 6 hours minimum. Apply 1 coat of Portola's All Purpose Base Coat by brush, roller or spray. Allow to dry for 6 hours between coats.

APPLICATION

Before applying Florentine Glaze, apply 1 or 2 coats of Portola's Zero VOC Eggshell acrylic in desired color by brush or roller. Allow to dry thoroughly. Application of Florentine Glaze: Thoroughly mix Florentine Glaze prior to application. Apply one coat of Florentine Glaze by brush and then work to achieve required finish, i.e. ragging, stippling, dragging or sponging. Allow a minimum of 8 hours dry time. Florentine Glaze remains "workable" for 5 to 10 minutes depending on temperature and humidity.

FINISH/DURABILITY

Portola's Florentine Glaze dries to a gloss finish.

COVERAGE RATES

Florentine Glaze covers approximately 100-130 square feet

per quart, depending on surface texture.

PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Store at room temperature in a dark area. Check color before use.

TECHNICAL DATA

Water based acrylic paint.

WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.