



**P O R T O L A**  
*Paints & Glazes*

PROUDUCT NAME

LIMEPROOF UNDERCOAT

Portola Paints & Glazes  
8213 W 3rd Street  
Los Angeles, CA 90048  
ph: 323.655.2211

[www.portolapaints.com](http://www.portolapaints.com)

PRODUCT DESCRIPTION

Portola's Limeproof Undercoat was created for use with Portola's Lime Wash. Portola's Limeproof Undercoat can be used over previously painted interior and exterior surfaces. Portola's Limeproof Undercoat is an acrylic primer made with 100% acrylic resin and formulated exclusively for Portola Paints & Glazes. Clean up is with water.

SUGGESTED APPLICATIONS

Portola's Lime Wash requires the use of Portola's Limeproof Undercoat. Spot prime where needed. For best results 2 coats are recommended.

LIMITATIONS

Portola's Limeproof Undercoat is not recommended for below grade use, for application to frost covered surfaces or for application below 50 degrees Fahrenheit. When used externally protect final coat from rain, frost and low temperatures for 48 hours after application.

GENERAL APPLICATION

PREPARATION

All loose or defective concrete or masonry and any surface contaminants such as dirt, grease, oil, acid, mildew, chalk, excessive salt, and efflorescence that adversely affect product adhesion and performance must be removed. Fresh cementitious substrates should be cured a minimum of 21 days prior to application.

Painted semi-gloss surfaces should be de-glossed and cleaned prior to use.

APPLICATION

Apply by brush, roller or spray. On stucco, roll or spray at a rate of 200 to 300 square feet per gallon. If sprayed, apply liberally and then back roll. Allow to dry for a minimum of 2 hours then apply a second coat.

COVERAGE RATES

Portola's Limeproof Undercoat covers up to 400 square feet per gallon on smooth surfaces and 200-300 on rough, textured or porous surfaces.

PACKAGING

Portola's Limeproof Undercoat is available in 1 quart, 1 gallon and 5 gallon quantities.

PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Store at room temperature.

TECHNICAL DATA

Acrylic water based paint.

WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied

here is given in good faith. There is no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.