



## PORTOLA

Paints & Glazes

### PRODUCT NAME

## LOW SHEEN ACRYLIC

---

Portola Paints & Glazes  
Studio City, California  
Phone: 818.623.9053  
www.portolapaints.com

### PRODUCT DESCRIPTION

Portola's Low Sheen Acrylic is a premium interior and exterior finish suitable for most paintable surfaces. Portola's Low Sheen Acrylic is available in wide variety of stock and custom colors.

### SUGGESTED APPLICATIONS

Portola's Low Sheen Acrylic may be applied to any paintable surface, including: wood, masonry, metal, brickwork, dry wall, plaster, architectural building products such as pre-cast stone, pre-fabricated columns and siding. After correct surface preparation, Low Sheen Acrylic may also be applied over previously painted surfaces.

### LIMITATIONS

Portola's Low Sheen Acrylic should not be applied below 50 degrees

Fahrenheit. When used externally protect final coat from rain, frost and low temperatures for 48 hours after application.

### GENERAL-APPLICATION

#### PREPARATION

All loose or defective concrete or masonry and any surface contaminants such as dirt, grease, oil, acid, mildew, chalk, excessive salt, and efflorescence that adversely affect product adhesion and performance must be removed. Fresh cementitious substrates should be cured a minimum of 21 days prior to application. Painted semi-gloss surfaces should be de-glossed and clean prior to priming with Portola's All Purpose Base Coat. Spot prime all repaired areas using Portola's All Purpose Base Coat. Allow to dry for six hours minimum. Then apply 1 coat of Portola's All Purpose Base Coat by brush, roller or spray. Allow to dry for six hours between coats.

#### APPLICATION

Apply one or two coats of Portola's Low Sheen Acrylic coat by brush or roller. Allow to dry for six hours between coats.

#### FINISH/DURABILITY

Low Sheen finish, washable and incredibly durable.

#### COVERAGE RATES

Portola's Low Sheen Acrylic covers approximately 300 to 400 square feet per gallon depending on porosity and texture of the surface.

### PACKAGING

Portola's Low Sheen Acrylic is available in 1 quart, 1 gallon and 5 gallon quantities.

### PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use. Store at room temperature.

### TECHNICAL DATA

Acrylic water based paint.

### WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.