



# PORTOLA

*Paints & Glazes*

## PRODUCT NAME

### MATTE WALL SEALER

Portola Paints & Glazes  
Studio City, California  
Phone: 818.623.9053  
[www.portolapaints.com](http://www.portolapaints.com)

## PRODUCT DESCRIPTION

Portola's Matte Wall Sealer is a clear, matte finish that is non-toxic, super durable and will not yellow over time.

Matte Wall Sealer is designed for use with Portola's Lime Wash, Wrought Iron Finish, Coppersmith, and Distemper. Matte Wall Sealer can also be used for sealing wood or concrete. This premium quality product is formulated with ingredients that screen out the destructive ultra violet rays.

## SUGGESTED APPLICATION

Portola's Matte Wall Sealer can be used on both interior and exterior surfaces and over Portola finishes.

## LIMITATIONS

Portola's Matte Wall Sealer should not be applied below 50 degrees

Fahrenheit. When used externally protect final coat from rain, frost and low temperatures for 48 hours after application.

## GENERAL-APPLICATION

### APPLICATION

Matte Wall Sealer can be applied by brush, roller or spray. For best durability, two coats are recommended. Clean up with water.

### FINISH/DURABILITY

Matte finish, wipeable, and creates an incredibly durable surface over Portola Finishes.

### COVERAGES RATES

Portola's Matte Wall Sealer covers up to 400 square feet per gallon on smoother surfaces and up to 150 to 300 square feet per gallon on rough textured or porous surfaces.

### PACKAGING

Portola's Matte Wall Sealer is available in 1 quart and 1 gallon quantities.

### PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Store at room temperature.

### TECHNICAL DATA

Acrylic water based sealer.

## WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.