



P O R T O L A
Paints & Glazes

PROUDUCT NAME
ROMAN CLAY

Portola Paints & Glazes
8213 W 3rd Street
Los Angeles, CA 90048
ph: 323.655.2211
www.portolapaints.com

PRODUCT DESCRIPTION

Portola's Roman Clay is a trowel applied wall finish that replicates the aged plaster walls found in the ancient villas of Tuscany. Roman Clay gives a wonderful depth of color and rustic originality to interior wall surfaces. Roman Clay is available in a broad range of standard and cutom colors.

SUGGESTED APPLICATIONS

Roman Clay is designed for smooth interior wall surfaces. Apply Roman Clay over properly prepared drywall, or plaster (see preparation). New and previously painted surfaces should be primed with one coat of Portola's All Purpose Basecoat.

LIMITATIONS

Portola's Roman Clay should not be applied below 50 degrees Fahrenheit.

GENERAL APPLICATION PREPARATION

Complete the painting of all adjacent surfaces, i.e. joinery, prior to application. All loose or defective concrete or masonry and

any surface contaminants such as dirt, grease, oil, acid, mildew, chalk, excessive salt, and efflorescence that adversely affect product adhesion and performance must be removed. Fresh cementitious substrates should be cured a minimum of 21 days prior to application. Painted semi-gloss surfaces should be de-glossed and cleaned prior to applying Portola's All Purpose Basecoat. Spot prime all repaired areas using All Purpose Basecoat by brush, roller or spray. Allow to dry for six hours between coats.

APPLICATION

First Coat: Apply a thin coat of Roman Clay (max 1/16") with a trowel or drywall knife. It is not necessary to achieve complete uniform coverage with the first coat.

Second Coat: Allow the first coat to dry over night. Remove any burs or rough spots by using a drywall knife and/or 220-320-grit sand paper. Apply a thin second coat to achieve complete coverage. It is important to note that in addition to product composition, further color range is achieved by varying the thickness of the material as it is applied. Allow the final coat to dry over night before applying finish. Remove any burs or rough spots by using 400-grit or finer sandpaper.

Finish: For a matte finish, Roman Clay can be left unsealed as is. For a washable, durable finish with a low sheen, apply one coat of Portola's Roman Clay Topcoat using a 6" putty knife. If a high gloss, polished finish is desired, apply one coat of Portola's Wall Wax using a 6" putty knife, allow to dry over night, and then polish until desired sheen is achieved. Colors will noticeably deepen because of the natural qualities of the Wall Wax. To prevent color change, apply one coat of Portola's Roman Clay Topcoat, allow to dry 4-6 hours, then apply one coat of

Portola's Wall Wax. Once dry, Wall Wax may be polished until desired sheen is achieved.

FINISH/DURABILITY

Roman Clay provides an extremely durable surface when finished with Portola's Roman Clay Topcoat or Portola's Wall Wax.

COVERAGE RATES

Portola's Roman Clay covers approximately 50-60 square feet per kilogram.

AVAILABLE SIZES

Portola's Roman Clay is available in 1, 4, 10 and 20 kilogram containers.

PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Store at room temperature in a dark area. Check color before use. Store at room temperature.

TECHNICAL DATA

Plaster, gypsum based.

WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.