



PROUDCT NAME  
ROYAL SATIN

Portola Paints & Glazes  
8213 W 3rd Street  
Los Angeles, CA 90048  
ph: 323.655.2211

[www.portolapaints.com](http://www.portolapaints.com)

PRODUCT DESCRIPTION

Portola's Royal Satin brings the rich luster of satin fabric to a paint finish for interior use. Royal Satin is available in 17 luxurious pearlescent colors and is also available in custom colors upon request.

SUGGESTED APPLICATIONS

Royal Satin is optimum for interior wood trim and furniture. For a great wall treatment, combine Royal Satin with Portola's Zero VOC Ultra Flat Acrylic in alternating vertical stripes. Sponging Royal Satin will give a tortoise shell finish.

LIMITATIONS

Portola's Royal Satin should not be applied below 50 degrees Fahrenheit. Due to the pearlescent quality of Royal Satin, application techniques will be visible. Use brush or effect roller to create different surface patterns depending on desired finished look.

GENERAL APPLICATION PREPARATION

All loose or defective concrete or masonry and any surface contaminants such as dirt, grease, oil, acid, mildew, chalk, excessive salt, and efflorescence that adversely affect product adhesion and performance must be removed. Fresh cementitious substrates should be cured a minimum of 21 days prior to application.

Painted semi-gloss surfaces should be de-glossed and cleaned prior to priming with Portola's Zero VOC All Purpose Basecoat. Spot prime all repaired area using Portola's Zero VOC All Purpose Basecoat. Allow to dry for 6 hours between coats.

APPLICATION

Apply 2 coats of Royal Satin by brush, roller or spray and allow a minimum of 6 hours dry time between coats. Royal Satin can also be applied by sponge, stipple brush, or fine texture roller to achieve special effects.

FINISH/DURABILITY

High sheen/reflective, washable, and incredibly durable.

COVERAGE RATES

Portola's Royal Satin covers approximately 90 square feet per quart.

PACKAGING

Portola's Royal Satin is available in 1 quart and 1 gallon quantities.

PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Store at room temperature in a dark area.

TECHNICAL DATA

Acrylic, water based paint.

WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There is no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.