



## PORTOLA

Paints & Glazes

### PROUDCT NAME SANDSTONE

Portola Paints & Glazes  
8213 W 3<sup>rd</sup> Street  
Los Angeles, CA 90048  
ph: 323.655.2211  
[www.portolapaints.com](http://www.portolapaints.com)

### PRODUCT DESCRIPTION

Portola's Sandstone is a totally unique 100% acrylic paint that is completely matte and richly textured to create a suede-like finish. Sandstone will not age or weather like Lime Wash, but retains the same beautiful texture and softness. Portola's Sandstone contains unique "micro-ceramic" technology that allows most household stains to be wiped away with warm soap and water. It is formulated for excellent hide, touch-up and ease of application and provides superior durability and years of trouble-free protection for interior and exterior applications. This is a Zero VOC product manufactured with no known carcinogens. It emits a low odor and is environmentally friendly. Sandstone is available in a wide variety of stock and custom colors.

### SUGGESTED APPLICATIONS

Portola's Sandstone has been specially formulated for interior and exterior applications. It may be applied to any paintable surface, including: wood, masonry, metal, drywall, plaster, architectural

building products such as pre-cast stone, pre-fabricated columns and siding. After correct surface preparation, Sandstone may also be applied over previously painted surfaces. When using Lime Wash on exteriors, Portola's Sandstone can be matched with the Lime Wash colors and is an excellent choice for use on gutters, downspouts and wood trim. Touching up Sandstone will not affect color.

### LIMITATIONS

Portola's Sandstone should not be applied below 50 degrees Fahrenheit. When used externally protect final coat from rain, frost, and low temperatures for 48 hours after application.

### GENERAL

#### APPLICATION/PREPARATION

Complete the painting of all adjacent surfaces, ie. joinery, prior to application. All loose, defective concrete or masonry and any surface contaminants such as dirt, oil, grease, acid, mildew, chalk, excessive salt and efflorescence that adversely affect the product adhesion and performance should be removed. Fresh cement based and plaster based substrates should be cured a minimum of 21 days prior to application. Painted semi-gloss surfaces should be deglossed and cleaned prior to applying 2 coats of Portola's All Purpose Base Coat. Spot prime all repaired areas using Portola's All Purpose Base Coat. For very deep colors primer may need to be tinted. Allow to dry for 6 hours minimum. Apply 1 coat of Portola's All Purpose Base Coat by brush, roller or spray. Allow to dry for 6 hours between coats.

#### APPLICATION

Apply one or two coats of Portola's Sandstone by brush or roller. Allow 6 hours drying time between coats.

Sandstone can also be applied using the Lime Wash application process (criss-cross or 'crows feet' brushing) to achieve a textured affect. Not recommended for spray application, as aggregate in paint will damage spray tips.

### FINISH/DURABILITY

Portola's Sandstone provides an extremely durable matte, textured finish.

### COVERAGE RATES

Portola's Sandstone covers approximately 300-400 square feet per gallon, depending on porosity and texture of the surface.

### PACKAGING

Portola's Sandstone is available in 1 quart, 1 gallon and 5 gallon quantities.

### PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use. Store at room temperature.

### TECHNICAL DATA

Acrylic based, water based, with aggregate.

### WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There is no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.