



**P O R T O L A**  
Paints & Glazes

PROUDUCT NAME  
ULTRA FLAT ACRYLIC

Portola Paints & Glazes  
8213 W 3<sup>rd</sup> Street  
Los Angeles, CA 90048  
ph: 323.655.2211  
[www.portolapaints.com](http://www.portolapaints.com)

PRODUCT DESCRIPTION

Portola's Ultra Flat Acrylic is a premium quality 100% acrylic "ceramic" finish suitable for most paintable surfaces, creating rich density and depth of color. Ultra Flat Acrylic contains unique "micro-ceramic" technology that allows most household stains to be wiped away with warm soap and water. It is formulated for excellent hide, touch-up and ease of application and provides superior durability and years of trouble-free protection for interior and exterior applications. This product is a Zero VOC product manufactured with no known carcinogens. It emits a low odor and is environmentally friendly. Portola's Ultra Flat Acrylic is available in a wide variety of stock and custom colors.

SUGGESTED APPLICATIONS

Portola's Ultra Flat Acrylic may be applied to any paintable surface, including wood, masonry, metal, drywall, plaster, architectural building products such as pre-cast stone. After correct surface preparation, Ultra Flat Acrylic may also be applied over previously painted surfaces.

LIMITATIONS

Portola's Ultra Flat Acrylic should not be applied below 50 degrees Fahrenheit. When used externally protect final coat from rain, frost, and low temperatures for 48 hours after application.

GENERAL

APPLICATION/PREPARATION

Complete the painting of all adjacent surfaces, e.g. joinery, prior to application. All loose, defective concrete or masonry and any surface contaminants such as dirt, oil, grease, acid, mildew, chalk, excessive salt and efflorescence that adversely affect the product adhesion and performance should be removed. Fresh cement based, plaster based substrates should be cured a minimum of 21 days prior to application. Painted semi-gloss surfaces should be de-glossed and cleaned prior to applying 2 coats of Portola's All Purpose Base Coat. Spot prime all repaired areas using Portola's All Purpose Base Coat. For very deep colors primer may need to be tinted. Allow to dry for 6 hours minimum. Apply 1 coat of Portola's All Purpose Base Coat by brush, roller or spray. Allow to dry for 6 hours between coats.

APPLICATION

Apply one or two coats of Portola's Ultra Flat Acrylic by brush or roller. Allow to dry for 6 hours.

FINISH/DURABILITY

Ultra Flat finish, washable and incredibly durable.

COVERAGE RATES

Portola's Ultra Flat Acrylic covers approximately 300-400 square feet per gallon, depending on porosity and texture of the surface.

PACKAGING

Portola's Ultra Flat Acrylic is available in 1 quart, 1 gallon and 5 gallon quantities.

PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use. Store at room temperature.

TECHNICAL DATA

Acrylic, water based, non-toxic.

WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There is no implied conditions or warranty in the supply of this product. The manufacturer's gaurantee is limited to product replacement only and does not include surface preparation or application.