



P O R T O L A
Paints & Glazes

PRODUCT NAME

WROUGHT IRON FINISH

Portola Paints & Glazes
Studio City, California
Phone: 818.623.9053
www.portolapaints.com

PRODUCT DESCRIPTION

Wrought Iron Finish contains actual iron filings and gives any paintable surface the look & feel of authentic Wrought Iron. With the application of Portola's Rust Solution, the Wrought Iron base becomes instantly rusted and corroded, enabling you to give any surface a rustic & aged finish.

SUGGESTED APPLICATIONS

Wrought Iron Finish may be applied to wood, plastic, masonry or any paintable surface. Wrought Iron Finish may be used on metal if a rust proof primer is used first. This coating is suitable both for interior or exterior surfaces.

LIMITATIONS

Wrought Iron Finish or Rust Solution should not be applied below 50 degrees Fahrenheit. When used externally protect final coat from rain, frost and low temperatures for 48 hours after application.

PREPARATION

Complete the painting of all adjacent surfaces, e.g. joinery, prior to application. All loose or defective concrete or masonry and any surface contaminants such as dirt, grease, oil, acid, mildew, chalk, excessive salt, and efflorescence that adversely affect product adhesion and performance must be removed. Fresh cementitious substrates should be cured a minimum of 21 days prior to application. Painted semi-gloss surfaces should be de-glossed and clean prior to priming with Portola's All Purpose Base Coat. Spot prime all repaired areas using Portola's All Purpose Base Coat. For very deep colors primer may need to be tinted. Allow to dry for six hours minimum. Apply 1 coat of Portola's All Purpose Base Coat by brush, roller or spray. Allow to dry for six hours between coats.

APPLICATION

Thoroughly mix Portola's Wrought Iron Finish before use to ensure even distribution of iron particles. Apply one coat Wrought Iron Finish with a brush and allow to dry thoroughly. It is important to achieve good coverage and that there are no areas where the product is applied too thinly. Apply Rust Solution with a disposable chip brush. Allow 12 hours dry time to achieve desired degree of rust. You may apply additional coats of Rust Solution to enhance rust effect.

FINISH/DURABILITY

Rust Solution will continue to rust after initial application. On interior surfaces, to protect and/or preserve the desired effect, coat with Portola's Matte Wall Sealer. Coating with this matte sealer can slow or stop further rusting;

therefore surface should be allowed to achieve desired finish before clear coating. The finish may change slightly; we recommend you select a small, hidden area to try first. For areas that come into contact with oils (ex. hand rails, door hardware) seal with a lacquer based clear coat.

COVERAGE RATES

Wrought Iron Finish covers approximately 65 square feet per quart depending on porosity and texture of the surface.

PACKAGING

Portola's Wrought Iron Finish is available in 1-quart and 1-gallon quantities. Portola's Rust Solution is available in 8-ounce containers.

PRECAUTIONS

Keep out of reach of children. Avoid swallowing. Avoid contact with eyes. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Store at room temperature in a dark area. Wear rubber gloves and splash goggles during use of Rust Solution.

TECHNICAL DATA

Acrylic water based paint with iron filings.

WARRANTY

Portola Paints & Glazes warrants its products to be of the highest quality. The information supplied here is given in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation or application.